

Notes -

A

1. Final Position Of Signs To Be Agreed On Site
2. Traffic Management Will Be In Accordance With Chapter 8 TSM And TSRGD 2016 Or Any Amendments thereto

TRAFFIC CONE ●

TRAFFIC SIGN ●



DETAIL B

- 40mph or less - 450mm traffic cones, spacing 1.5m.
- 50mph or more - 750mm traffic cones, spacing 1.5m.
- Motorways and NSL dual with hardshoulders - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:
1) During darkness, regulation 55 lamps should be provided at 9m centres, relaxation for 40mph or less - 10m.
2) 45° tapers have 1.5m spacing, no relaxations.
3) On motorways and NSL dual with hardshoulders use 1m cones for lead tapers and facing wall of lane changes.

Approval For Construction

This drawing is deemed to be submitted for approval by the specified parties in accordance with the contract. Please confirm approval as soon as possible prior to the installation of the layout detailed on this drawing. If no negative comments and/or a rejection is received from the specified parties within the contracted period or prior to the proposed date of installation whichever is the soonest then the drawing will be deemed as approved.

Hurst Lane

road closure

Client Tarmac			
Drawn by J.O	Checked by J.M.B	Submitted for approval P Wilcox	Authorised by Date
Date 20.04.18	Date 20.04.18	Date 20.04.18	Date
Contract No. J042 159017/042		Scale N.T.S	
Drawing No. TM-J042159017/042/rc1		Client Ref No. N/A	

